



## NEO BATTERY LINE

### NEO-9 MINI



The ultimate 98wh Li-Ion pack  
for Digital Cinema

Capacity: 98Wh (14.8v, 6.6Ah)  
Operational Voltage: DC 12v-16.8v  
Size: 3.54" x 4.65" x 1.90"  
Weight: 1.4lbs.  
Normal Runtime: (25w) 3.6hrs.  
Load: 16A peak/12A continuous  
Ptap & USB 5v

### NEO-98 SLIM



30% slimmer than our original  
12Amp High Draw

Capacity: 98Wh (14.8v, 6.6Ah)  
Operational Voltage: DC 12v-16.8v  
Size: 3.8" x 5.87" x 1.49"  
Weight: 1.4lbs.  
Normal Runtime: (25w) 3.6hrs.  
Load: 16A peak/12A continuous  
Ptap & USB 5v

## NEO 150

All Models available in 3 Stud and V-Mount



### NEO-150 MINI



147wh of power for Cinema

Capacity: 147Wh (14.8v, 9.9Ah)  
Operational Voltage: DC 12v-16.8v  
Size: 3.54" x 4.65" x 2.38"  
Weight: 1.8lbs.  
Normal Runtime: (25w) 5.9hrs.  
Load: 16A peak/12A continuous  
Ptap & USB 5v



Compact, robust and lightweight.  
Sustains up to 16A peak loads, and 12A continuous.  
USB firmware programmable. More intuitive LCD.  
All the features of Hypercore.

Simply, the perfect 14v pack.

# NEO BATTERY FEATURES



Modular Build



Smart Tap



USB Power



2K Cycles  
2Y Warranty



High Current  
Delivery



Firmware  
Upgradeable



Runtime LCD



LED Gauge



Compatible  
Charging



Camera  
Communication



UN38.3 Certified



Hibernation



RFID



Rubberized  
Housing



Storage Mode

Contact us for more details on our products at  
[www.coreswx.com](http://www.coreswx.com)



New York HQ  
91B Commercial Street  
Plainview NY, 11803 USA  
Tel: +1 (516) 595-7488

Core LA  
2535 W 237th St  
Ste 127  
Torrance, CA 90505 USA  
Tel: +1 (424) 250-9270

