



# NANO

MICRO

BATTERY LINE

**NANO-V98**

**NANO-G98**



**Super compact,  
highly versatile,  
98Wh pack**



Capacity: 98Wh(14.8v, 6.6Ah)  
Operational Voltage: DC 12v-16.8v  
Size: 2.82" x 3.93" x 1.94"  
Weight: 1.2 lbs.  
Normal Runtime: (25w) 3.6hrs.  
Load: 10A

**NANO-V150**

**NANO-G150**



**NANO Micro Size,  
Neo Power Delivery**



Capacity: 147Wh(14.8v, 9.9Ah)  
Operational Voltage: DC 12v-16.8v  
Size: 2.82" x 3.93" x 2.63"  
Weight: 1.52 lbs.  
Normal Runtime: (25w) 5.9hrs.  
Load: 16A peak/12A continuous

**NANO-V50**

**NANO-G50**



**Most compact Micro  
pack on the market**



Capacity: 49Wh(14.8v, 3.3Ah)  
Operational Voltage: DC 12v-16.8v  
Size: 2.82" x 3.93" x 1.49"  
Weight: 0.8lbs.  
Normal Runtime: (25w) 1.8hrs.  
Load: 6A



UN38.3 Certified



Storage Mode



Compatible  
Charging



Camera  
Communication



P Tap



USB Power



LED Gauge



Hibernation

# NANO MICRO ACCESSORIES

V - MOUNT

CXVM-FX6



A V-mount micro-style power option for the Sony FX6

CXV-C3MK



Direct mount for Canon EOS Cine cameras with DC 4-pin XLR input

CXV-KOMU



**RED**  
APPROVED

BP to V-mount plate direct mount for RED Komodo

GPTS-MICRO



Micro Hot-Swap Dual V-mount Battery Plate

3 - STUD

CXAM-FX6



A 3-Stud micro-style power option for the Sony FX6

CXA-C3MK



Direct mount for Canon EOS Cine cameras with DC 4-pin XLR input

CXA-KOMU



**RED**  
APPROVED

BP to V-mount plate direct mount for RED Komodo

GPTA-MICRO



Micro Hot-Swap Dual 3-Stud Battery Plate

Contact us for more details on our products at

[www.coreswx.com](http://www.coreswx.com)



New York HQ  
91B Commercial Street  
Plainview NY, 11803 USA  
Tel: +1 (516) 595-7488

Core LA  
2535 W 237th St  
Ste 127  
Torrance, CA 90505 USA  
Tel: +1 (424) 250-9270

