



Designed to finally answer the call for a tailored on-board battery solution, the Apex battery packs are the ideal power solution for high power LED lighting.

The Apex packs offer a 367wh Lithium Ion v-mount solution capable of outputting up to 24A continuously as well as providing extended runtimes. With Apex the production team can focus on the video production rather than restricting light usage during the production because of limiting on-board powering options. And with the up to 24A load output, the user will enjoy a more "true" runtime while operating the high power LED lighting systems.



### APX-360V

Capacity: 367Wh (14.8v, 25.5Ah)  
 Operational Voltage: DC 12v-16.8v  
 Size: 3.5" x 6.3" x 3.8"  
 Weight: 3.6 lbs  
 Load: 24A Continuous  
 Mount type: Standard V-mount



### APX-360HV

Capacity: 367Wh (29.6v, 12.75Ah)  
 Operational Voltage: DC 22v-33.6v  
 Size: 3.5" x 6.3" x 3.8"  
 Weight: 3.6 lbs  
 Load: 12A Continuous  
 Mount type: Helix V-mount

## CHARGERS



### GP-X2RV

Input: 100V-240VAC 50/60Hz  
 Charge current: One pack 5.2A @16.8v,  
 Two packs simultaneous at 2.6A  
 Size: 4.5" x 5.5." x 3"  
 Weight: 1.3lb.  
 Mount Type: V-mount



### GP-X2RHV

Input: 100V-240VAC 50/60Hz  
 Charge current: One pack 2.6A @33.6v,  
 Two packs simultaneous at 1.3A  
 Size: 4.5" x 5.5." x 3"  
 Weight: 1.3lb.  
 Mount Type: Helix V-mount



## ACCESSORIES



### HLX-2HV-DC

Direct Connect for APX-360HV

Input: DC 11-34v  
Output for Light: DC 11-34v  
Size: 3.25" x 5.5" x 0.5"  
Weight: 0.4 lbs.



### APX-GP-S

G-mt to V-mt Plate for Apex

Input: DC 11-17v  
Output for Light: DC 11-17v, unregulated  
Size: 3.25" x 5.5" x 1.5"  
Weight: 0.7 lbs.



### HLX-2HV-DC

Riser Plate for Nanlite Ballast

Input: DC 11-17v  
Output for Light: DC 11-17v, unregulated  
Size: 3.25" x 5.5" x 1.5"  
Weight: 0.7 lbs.

## BUNDLES



### APX-360VK

Two APX-360V battery packs and one GP-X2RV dual charger

Capacity: 367Wh (14.8v, 25.5Ah)  
Operational Voltage: DC 12v-16.8v  
Load: 24A Continuous  
Charger Input: 100V-240VAC 50/60Hz  
Charge current: One pack 5.2A @16.8v,  
Two packs simultaneous at 2.6A  
Mount type: Standard V-mount



### APX-360HVK

High voltage solution for Aputure 600-series. Includes two APX-360HV, one GP-X2RHV, and HLX-2HV-DC

Capacity: 367Wh (29.6v, 12.75Ah)  
Operational Voltage: DC 22v-33.6v  
Load: 12A Continuous  
Charger Input: 100V-240VAC 50/60Hz  
Charge current: One pack 2.6A @33.6v,  
Two packs simultaneous at 1.3A  
Mount type: Helix V-mount

Contact us for more details on our products at

[www.coreswx.com](http://www.coreswx.com)



New York HQ  
91B Commercial Street  
Plainview NY, 11803 USA  
Tel: +1 (516) 595-7488

Core LA  
2535 W 237th St  
Ste 127  
Torrance, CA 90505 USA  
Tel: +1 (424) 250-9270

